

# Product data sheet

FLAT POLYMERO  
672059.002.5.04  
RZB




IP  
40

IK  
03


Series: FLAT POLYMERO Decorative round surface-mounted luminaire. For escape route illumination. Base: metal, powder-coated. Diffuser made of non-yellowing plastic (PMMA), opal. Diffuser fastening: patented push system. Suitable for ceiling mounting, wall (surface). Self-contained system with automatic self-test and feedback to the RZB monitoring system MULTIDIGIT. Colour: white Diameter: 460mm Height: 120mm Weight: 2.44kg Operating mode: Non-maintained power mode and maintained power mode Duration time: 3h Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 20W Rated luminous flux: 2100lm Luminous flux, emergency: 200lm System power, emergency: 0W Control gear: Regulated power supply Protection class: I Type of protection: IP40

## Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	20 W	CRI	80
Total flux	200 lm	LOR	100%
Luminous efficacy	10 lm/W	ULOR	10%
		Total power	20 W

## Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	20 W	CRI	80
Total flux	2100 lm	LOR	100%
Luminous efficacy	105 lm/W	ULOR	10%
		Total power	20 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Height: 4.72 in  
Diameter: 18.11 in

## Electric

System power: 40 W

## Information regarding emergency functions

Supplementary emergency lighting  
Emergency sign: N/A

## Adjustability

Fixed

## Protection

IP: 40

IK: 03