
Product data sheet

LINEAR LIGHTING

V1-R0-72822-02OPD-4002340 X-LINE 0,75 M STAND-ALONE 23W 4000K DALI


VARTON



IP 40 IK 01

• Extruded aluminum luminaire • Standalone Application • Retail spaces • Administrative facilities Installation • Surface-mounted • Suspended Input voltage (AC, 50Hz): 176...264 AC frequency: 50 Flicker: 1 Climatic modification and category of placement: УХЛ4 Color rendering index: 80-89 Protection class: I Mounting method: Pendant Ingress protection (IP): IP40 Radiation angle: Radiation angle: 100 Impact resistance: IK01 Power factor: 0,95 https://www.varton.ru/products/lineynye-svetilniki-dlya-vnutrennego-osveshcheniya/x-line-odinochnye/x-line-0-75-m-odinochnye/svetodiodnyy-svetilnik-varton-kh-line-odinochnyy-podvesnoy-23-vt-4000-k-755x63x100-mm-ip40-ral7022-s/

Light output 1



1 x LED

Nominal lamp power	23 W	LOR	100%
Lamp flux	2300 lm	Total flux	2300 lm
Luminous efficacy	100 lm/W	Total power	23 W
CCT	4000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 29.72 in

Width: 2.48 in

Height: 3.94 in

Adjustability

Fixed

Electric

System power: 23 W

Protection

IP: 40

IK: 01