Product data sheet

INDUSTRIAL AND WAREHOUSE LIGHTING
V1-IA-70155-03AT1-6704440 IRON 2.0 1,5 M 44W 4000K TRANSPARENT EM 1H TELETEST
VARTON



IP 67 IK 01

Industrial linear luminaire with aluminium housing and a wide range of power. Diffuser: transparent (acrylic), opal (polycarbonate) Installation: Suspended and surface-mounted. Suspended 3-6 m height (mounting brackets included in package). Surface-mounted (mounting brackets included in package). The luminaire has a wire for connecting to the mains. Wire length 0.5 meter Application: Administrative facilities. Industrial facilities. Warehouses. Areas with high moisture and dust environment, and high reliability requirements. Power factor: 0,95 Input voltage (AC, 50Hz), V: 198...264 AC frequency, Hz: 50 Input voltage (DC), V: 190...280 Flicker, %: 5 Climatic modification and category of placement: УХЛ1 Protection class: I Ingress protection (IP): IP67 Impact resistance: IK01 https://www.varton.ru/products/promyshlennoe-i-skladskoe-osveshchenie/iron-2-0/iron-2-0-1-5-m/svetodiodnyy-svetilnik-varton-ayron-2-0-44-vt-4000-k-1475kh109kh66-mm-ip67-s-akril-rasseivatelem-ava/

Light output 1



1 x LED

Nominal lamp power	44 W	LOR	100%
Lamp flux	6370 lm	Total flux	6370 lm
Luminous efficacy	145 lm/W	Total power	44 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 58.07 in
Width: 4.29 in
Height: 2.60 in

Adjustability

Fixed

Electric

System power: 44 W

Protection

IP: 67
IK: 01