Product data sheet


MINGATA MINI
612171.0031.76
RZB



IP 66 IK 08

Series: MINGATA mini Functional pole-side and pole-top luminaire in a modern design. Housing made of corrosion-resistant die-cast aluminium, seawater-resistant powder-coated (C4, in accordance with ISO 12944-6). C5 coating available on request. Pole-top fixing with integrated cable routing and stainless steel screws. With membrane valve as a standard to avoid condensed water. Cover clear single-pane toughened glass. Asymmetrical light distribution. Luminaires for pole top Ø 76 mm (with optional adapter sleeve, also suitable for pole top Ø 60 mm). Tool-free maintenance / replacement by Eccentric-Lock system with disconnect plug and Hybrid-Lock-System. 4 x 1.0 mm² connecting cable included, length 8 m. Colour: anthracite metallic (DB703) Length: 530 mm Width: 270 mm Height: 100 mm Lamp: LED System power: 15 W Rated luminous flux: 2000 lm Luminous efficiency: 133 lm/W Control gear: Converter, dimmable, DALI Protection class: II Type of protection: IP 66

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	15 W	CRI	70
Total flux	2000 lm	LOR	28%
Luminous efficacy	133 lm/W	ULOR	8%
		Total power	15 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 10.63 in
Width: 20.87 in
Height: 3.94 in

Adjustability

Fixed

Electric

System power: 15 W

Protection

IP: 66
IK: 08