


Product data sheet


RETRO V LED
4.775.9008.07-2
LEIPZIGER LEUCHTEN



IP
65

recom. pole height: 3.50m – 6.00m light standards: low and medium lighting requirements lamp: excl. metal halide, sodium, compact fluorescent lamps; incl. 1 glare-free LLM LED module 1 , easy to replace colour temperature: 3.000K warm white or 4.000K neutral white gear: HCI and NAV: incl. low loss ballast, ignitor and condensator; electronic ballast on request; CDO, compact fluorescent lamps: incl. electronic ballast; LED: electronic driver up to 100.000 hours; LED: CLO mode LED life expectancy: up to 50.000 hours/ L100 light control: at extra cost: dimming; power reduction; LED: CLEVER LIGHT 10 optical system: reflector system for directed, horizontally mounted ellipsoid, coated lamps (except for CPO); LED: reflector system for directed, horizontally mounted LLM LED modules light distribution: asymmetrical wide beam; LLM LED: extreme wide beam luminaire head: made of aluminium with a special white, reflective underside finish; powder coated bracket: incl. decorative semicircular bracket for post tops resp. WL: made of stainless steel, with wall shield made of hot dip galvanised steel, powder coated colour: RAL or DB glazing: polycarbonate, clear or pearl structured, impact resistant, UV-stabilised wiring: luminaire head completely wired, incl. cable: 1 bracket: ca. 2.00m; via a plug and socket connector below the bracket; 2 brackets: incl. cable until access door; WL: ca. 2.00m, via a plug and socket connector within the wall shield; installation: 1 or 2 brackets: for post top \varnothing 76mm or \varnothing 60mm; RETRO V: for post top \varnothing 76mm or \varnothing 60mm with 6 threads M8; RETRO VIII: for tubular column only; WL: to be screwed to the wall accessory: lamp (except LED), cable, column, pole accessories, wall fixing materials – to be ordered separately application areas: residential and local distribution roads, car parks, schools, hotels, factory premises, paths, squares, parks

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	20 W	CRI	70
Total flux	1618 lm	LOR	100%
Luminous efficacy	81 lm/W	ULOR	5%
		Total power	20 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 15.35 in
Diameter: 21.42 in
Weight: 11.5 kg

Adjustability

Height adjustable

Electric

System power: 20 W

Protection

IP: 65