Product data sheet


NADJA III (WALL FITTING) 9.846.3066.05 LEIPZIGER LEUCHTEN





Recommended mounting height 3.50 - 5.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp				
Nominal lamp power	125 W	LOR		

Lamp flux	6800 lm	Total flux	5317 lm
Luminous efficacy	39 lm/W	Total power	137 W
CCT	3400 K		
CRI	54		

4	XXWXAH
X	
\bigcirc	
$\langle \cdot \rangle$	XTTXX
\searrow	THY
\mathcal{L}	THE

1 x High pressure mercury vapour lamp					
Nominal lamp power	80 W	LOR	78%		
Lamp flux	4000 lm	Total flux	3128 lm		
Luminous efficacy	35 lm/W	Total power	89 W		
CCT	3400 K				
CRI	54				

Electric
System power: 89-137 W
Ballast: ECG
Protection
IP: 55
Designation labels: CE
Other operating numbers
Ambient temperature range: 3295°F

Created by luminaires.dialux.com (17 May, 2024)

78%