

Product data sheet


SLOIN T SL IP54 LED3600-830 L2813 PCO
42185600
ZUMTOBEL



IP
54

LED light line in IP54 with DALI-controllable LED converter; LED service life lasts 50000 h before luminous flux is reduced to 90% of the initial value. Chromaticity tolerance (initial MacAdam): 3. Luminaire luminous flux: 3725 lm, Luminaire efficacy: 86 lm/W. Colour rendering Ra > 80, colour temperature 3000 K. PC cover with anti-glare film for standard-compliant workstation illumination with UGR<19 and L65<3000 cd/m² (EN: 12464:2011). Luminaire of aluminium, white powder coated. Luminaire with completely uniform appearance due to polycarbonate cover. Luminaire consists of housing and continuous optic of polycarbonate. For installing in module ceilings with 12 mm edges and for installing in plasterboard ceilings. Armstrong® TECH ZONE compatible with ceiling types with width 100 mm. Includes gear tray, wiring, and end-cap set. Luminaire wired with halogen-free leads and covers are due to norm classified as TP(a). Degree of protection: IP54. Dimensions: 2813 x 100 x 134 mm weight: 8.6 kg

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	43.3 W	CRI	80
Total flux	3725 lm	LOR	100%
Luminous efficacy	86 lm/W	Total power	43.3 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 110.75 in
Width: 3.94 in
Height: 5.28 in
Weight: 8.6 kg

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 43.3 W
Voltage: 220-240 V AC
Controller: DALI

Protection

IP: 54