Product data sheet

LUMISTREET GEN2 BGP293 T25 1 XLED80-4S/740 DRXN0
BGP291
PHILIPS



Time to upgrade your conventional lighting to LumiStreet gen2 Increasing numbers of municipalities are having to upgrade large-scale conventional street lighting installations with energy efficient LED technology. But they are having to do this with smaller and smaller budgets. That's why the new generation of LumiStreet has been upgraded and designed to provide a solution to this challenge, it is the ideal solution for performing point-to-point replacement of conventional lighting. LumiStreet gen2 achieves this by offering high efficiency, low Total Cost of Ownership, and ease of installation and maintenance. The ease of installation and maintenance is enabled by the Philips Service tag. Moreover, the Philips SR (System Ready) socket makes it future-ready and you can pair this luminaire with lighting control and software applications such as Interact City.

Light output 1



1 x LED

Nominal lamp power	46 W	LOR	88%
Lamp flux	8000 lm	Total flux	7003 lm
Luminous efficacy	152 lm/W	Total power	46 W
CCT	4000 K		
CRI	70		

Mounting mode

Pole top mounted

Shape and measurements

Length: 3.39 in
Width: 3.39 in
Height: 2.68 in

Design

Designer: Ruben Saldaña

Electric

System power: 46 W