



Product data sheet

LOUI 50
925344.0045.1
RZB



Series: LESS IS MORE 50;system Gerades Modulgehäuse Aluminium-Strangpressprofil pulverbeschichtet, stirnseitig offen zum weiter verdrahten zum Lichtbandsystem. Austauschbare und herausnehmbare LED-Einheit mit integriertem Betriebsgerät. Alea Optik System: Reflektorstruktur (ABS, Aluminium bedampft, hochglänzend) mit Diffusor aus vergilbungsfreiem Kunststoff (PMMA) opal für blendfreies Licht am Arbeitsplatz (UGR <19, Bildschirmgerecht gemäß DIN EN 12464-1). Nur optional: Lichtbandsystem vorbereitet für Seilabhngung! Colour: silver, matt (approx. RAL9006) Length: 1401;mm Width: 57;mm Height: 75;mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 35;W Rated luminous flux: 4450;lm Luminous efficiency: 127;lm/W Control gear: Regulated power supply Protection class: I Type of protection: IP20

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	35 W	CRI	80
Total flux	4450 lm	LOR	100%
Luminous efficacy	127 lm/W	Total power	35 W

Mounting mode

Ceiling mounted

Electric

System power: 35 W

Shape and measurements

Length: 2.24 in
Width: 55.16 in
Height: 2.95 in

Protection

IP: 20
IK: 03

Adjustability

Fixed