Product data sheet


SINUS SUSP. 'Y' WHITE PRISM. 1530MM
R33Y153-9016E1930H3M OHNE FOLIE/WITHOUT FOIL
PLANLICHT



IP 40


high output LED 3000K CRI 90 105,2W 12118lm¹ DALI ¹Values without foil [Luminaire is delivered with optional satined-foil for increased homogenity. The light distribution is thus influenced and the luminous flux is reduced by 26,3% https://katalog.planlicht.com/en-gb/fam-sinus/

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	13.15 W	CRI	90
Total flux	1515 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	13.15 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	13.15 W	CRI	90
Total flux	1515 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	13.15 W

Light output 3 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	13.15 W	CRI	90
Total flux	1515 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	13.15 W

Light output 4 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	13.15 W	CRI	90
Total flux	1515 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	13.15 W

Light output 5 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	13.15 W	CRI	90
Total flux	1515 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	13.15 W

Light output 6 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	13.15 W	CRI	90
Total flux	1515 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	13.15 W

Light output 7 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	13.15 W	CRI	90
Total flux	1515 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	13.15 W

Light output 8 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	13.15 W	CRI	90
Total flux	1515 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	13.15 W

Mounting mode

Pendant

Shape and measurements

Length: 60.24 in
Width: 60.24 in
Height: 3.94 in

Adjustability

Fixed

Electric

System power: 105.2 W

Protection

IP: 40