


Product data sheet

SLIM_3 LED_39W_COOL_WIDE_L1030MM
812221134
PETRIDIS



A linear LED luminaire which illuminates facades uniformly and emphasises their surfaces. Although buildings fade over time, the proper lighting can add value to them, highlight their uniqueness and make a lasting impression. Technical Features - Aluminium body. - Beam distribution lens. - Adjustable. - Safety glass cover. - Die cast aluminium and caps. - Silicone sealant. - Pure light without IR/UV radiation. - Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B10) (only for SLIM 3 - LED). - Supplied with 3x1mm NEOPRENE 1,5m cable. Upon request: Available with highest colour rendering index (CRI)

Light output 1



1 x LED			
Nominal lamp power	29 W	LOR	73%
Lamp flux	2964 lm	Total flux	2171 lm
Luminous efficacy	102 lm/W	Total power	29 W
CCT	6000 K		
CRI	80		

Mounting mode

Ceiling mounted, Floor mounted

Shape and measurements

Length: 40.55 in
Width: 1.85 in
Height: 1.73 in

Adjustability

Rotatable

Design

Material impression: Aluminum, Glass

Electric

System power: 29 W
Appliance Class: II

Protection

IP: 65
IK: 06
Resistant to impact of balls
Designation labels: CE