

Product data sheet

NADJA III (2-ARMED)
9.877.3046.05
LEIPZIGER LEUCHTEN



IP
55

Recommended mounting height 3.50 - 5.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711
Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp

Nominal lamp power	50 W
Lamp flux	2000 lm
Luminous efficacy	27 lm/W
CCT	3400 K
CRI	54

LOR	78%
Total flux	1564 lm
Total power	59 W




1 x High pressure mercury vapour lamp

Nominal lamp power	80 W
Lamp flux	4000 lm
Luminous efficacy	35 lm/W
CCT	3400 K
CRI	54

LOR	78%
Total flux	3128 lm
Total power	89 W


Light output 2



1 x High pressure mercury vapour lamp

Nominal lamp power	50 W
Lamp flux	2000 lm
Luminous efficacy	27 lm/W
CCT	3400 K
CRI	54

LOR	78%
Total flux	1564 lm
Total power	59 W



1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	78%
Lamp flux	4000 lm	Total flux	3128 lm
Luminous efficacy	35 lm/W	Total power	89 W
CCT	3400 K		
CRI	54		

Mounting mode

Pole top mounted

Electric

System power: 118-178 W

Shape and measurements

Height: 16.54 in

Diameter: 16.54 in

Protection

IP: 55