



# Product data sheet

MARCO LED  
10711844  
FLOS



• Square luminaire for outdoor installation on wall. • Configuration: die-cast aluminium structure. EN AB-47100 alloy (low copper content). • Double layer coating for high resistance to corrosion: The low copper Aluminium alloy is painted with a double coat using powders which are complaint with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents).The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. • Tempered glass with silkscreen border. The diffuser is fixed to the aluminium structure through a robotic gluing system. AISI 304 stainless steel fixing plate.

## Light output 1 (integrated)



Lamp type	LED	CCT	6000 K
Nominal lamp power	4 W	CRI	70
Total flux	103 lm	LOR	100%
Luminous efficacy	26 lm/W	ULOR	50%
		Total power	4 W

## Mounting mode

Wall mounted

## Shape and measurements

Length: 4.92 in  
Width: 4.92 in  
Height: 1.97 in

## Adjustability

Fixed

## Electric

System power: 4 W  
Appliance Class: II

## Protection

IP: 65  
IK: 02