Product data sheet

PASTRENGO 2
68064
EGLO



IP 20

ring light direct, wall and ceiling, black structured, DALI, opal cover

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	5.5 W	CRI	80
Total flux	330 lm	LOR	100%
Luminous efficacy	60 lm/W	Total power	5.5 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	5.5 W	CRI	80
Total flux	330 lm	LOR	100%
Luminous efficacy	60 lm/W	Total power	5.5 W

Light output 3 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	5.5 W	CRI	80
Total flux	330 lm	LOR	100%
Luminous efficacy	60 lm/W	Total power	5.5 W

Light output 4 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	5.5 W	CRI	80
Total flux	330 lm	LOR	100%
Luminous efficacy	60 lm/W	Total power	5.5 W

Light output 5 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	5.5 W	CRI	80
Total flux	330 lm	LOR	100%
Luminous efficacy	60 lm/W	Total power	5.5 W

Light output 6 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	5.5 W	CRI	80
Total flux	330 lm	LOR	100%
Luminous efficacy	60 lm/W	Total power	5.5 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 19.69 in

Width: 19.69 in

Height: 3.15 in

Adjustability

Fixed

Electric

System power: 33 W

Protection

IP: 20

Designation labels: CE