

Product data sheet

LOUIS I (WALL FITTING)
9.745.2036.07
LEIPZIGER LEUCHTEN




Mounting height of 3.00 to 4.50 m for medium light requirements - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Mirror lamellae for light guidance and glare limitation made of premium highest-grade aluminium, burnished and anodized - Aluminium reflector finished in special white paint for max. light reflection - Aluminium cover painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components arranged on a block - Connection with adapter jack - Available in any RAL or DB colour without surcharge
Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure sodium vapour lamp

Nominal lamp power	50 W	LOR	56%
Lamp flux	3500 lm	ULOR	14%
Luminous efficacy	32 lm/W	Total flux	1957 lm
CCT	2000 K	Total power	62 W
CRI	25		



1 x High pressure sodium vapour lamp

Nominal lamp power	70 W	LOR	56%
Lamp flux	5600 lm	ULOR	14%
Luminous efficacy	38 lm/W	Total flux	3131 lm
CCT	2000 K	Total power	83 W
CRI	25		

Mounting mode

Wall mounted, Ceiling mounted

Shape and measurements

Height: 7.87 in
Diameter: 7.87 in

Design

Material impression: Matt
Color of housing: White

Electric

System power: 62-83 W
Ballast: ECG
Controller: DALI

Protection

IP: 55
Designation labels: CE

Other operating numbers

Ambient temperature range: 5...95°F