# Product data sheet

CUDDLE MINI LED REG D4I X2 24 4000K LN
2228430/4/LN/10KV
ROSA



IP 66

One of the most frequently chosen luminaires. The basic version of the product from the CUDDLE MINI LED series. In a compact size, made of aluminium - in the standard version the body is anodised in inox and black. Installed on an extension arm with a ⌀ 60 x 100 mm ending. Most often, it illuminates city and residential streets, pedestrian routes and car parks. It has a protection class of IP 66 for the optical part and the power input system. The luminaire is equipped with PMMA lenses, an interchangeable LED module and a tempered glass diffuser. The expected service life of the product is L90B10 - 100,000. h. The input voltage frequency is 50/60Hz. Power factor ≥0.95. The fixture has 16 LEDs. It is possible to connect the luminaire to an external control system and/or sensors via a socket compatible with Zhaga Book 18.

## Light output 1



1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 26 W | LOR | 84% |
| Lamp flux | 4600 lm | Total flux | 3842 lm |
| Luminous efficacy | 177 lm/W | Total power | 26 W |
| CCT | 4000 K | | |
| CRI | 70 | | |

### Mounting mode

Pole top mounted

### Shape and measurements

Length: 25.39 in
Width: 8.11 in
Height: 3.07 in

### Adjustability

Free

### Electric

System power: 26 W

### Protection

IP: 66