


# Product data sheet

SAFELITE 20M,MAINS,IP65,200LM,SLAVE  
SL2-M65F0FMT  
EATON EMERGENCY LIGHTING




LED safety luminaire for all applications (Escape route, Anti-panic, Exit sign) • First fix base for ease of installation • High impact resistant (IK07) and high degree of protection (IP65) • Recessed mounting optional • Minimum service requirement due to high service life of the LEDs (up to 50,000 hours)

## Light output 1 (integrated)



Lamp type	LED	CCT	6500 K
Nominal lamp power	2.9 W	CRI	65
Total flux	200 lm	LOR	100%
Luminous efficacy	69 lm/W	Total power	2.9 W

## Light output 2 (integrated, emergency)



Lamp type	LED	CCT	6500 K
Nominal lamp power	2.9 W	CRI	65
Total flux	200 lm	LOR	100%
Luminous efficacy	69 lm/W	Total power	2.9 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 10.63 in

Width: 4.69 in

Height: 1.93 in

## Adjustability

Fixed

## Electric

System power: 5.8 W

Appliance Class: II

## Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

## Protection

IP: 65

IK: 07