


Product data sheet

LOG OUT UP/DOWN WL T16 2X28/54W MP
581-01546MP
MOLTO LUCE




Log OUT UP/DOWN T16, Wandleuchte direkt/indirekt strahlend; kantiges, geradliniges Aluminium Strangpressprofil; schwarz pulverbeschichtete Oberfläche, Abdeckung aus hochwertigem, klarem Polycarbonatprofil mit innenliegender Microprismen Abdeckung, blendfrei und bildschirmtauglich; Abdeckung für indirekten Anteil ist eine klare PC-Abdeckung für schattenfreie, homogene Lichtverteilung; 1x2x 28/54W T16 G5, 230V, Multiwatt EVG; IP20;

Light output 1



2 x Fluorescent lamp tubular T5

Nominal lamp power	54 W	Socket	G5
Lamp flux	4450 lm	LOR	48%
Luminous efficacy	79 lm/W	ULOR	27%
CCT	3000 K	Total flux	4291 lm
CRI	85	Total power	54 W



2 x Fluorescent lamp tubular T5

Nominal lamp power	28 W	Socket	G5
Lamp flux	2600 lm	LOR	48%
Luminous efficacy	46 lm/W	ULOR	27%
CCT	3000 K	Total flux	2507 lm
CRI	85	Total power	54 W

Mounting mode

Ceiling mounted, Wall mounted

Shape and measurements

Length: 46.46 in

Width: 2.36 in

Height: 5.71 in

Adjustability

Fixed

Electric

System power: 54 W

Appliance Class: I

Protection

IP: 20