


Product data sheet

RAX SURFACE 150 WHITE 19W 4000K RA>80
8246081649
SG ARMATUREN



Flush-mounted LED downlight. Made of fire-resistant polycarbonate. SDCM 2. L90/B10>50,000, Supplied with 3000K/4000K LED. Complete with driver and quick connection between driver and downlight for super quick and simple mounting. Can be mounted to ceiling panels with a thickness of 1–50 mm. The luminaire comes complete with ceiling ring RAL9010 gloss 25 made of die-cast aluminium. Matt reflector. Light distribution: Direct Light technic LED 19W 4000K Ra>80 SDCM 2 L90/B10 >50,000 hrs at Ta=25°C Control/Dimming On/Off Protection Class I IP20 Energy and approvals A++ CE Materials and finish Housing: Spun aluminium Colour: White Optics: Aluminium Mounting/Connection Surface, Indoor Max. luminaires per circuit breaker: B10: 21, B16: 34, C10: 35, C16: 58

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	19 W	CRI	80
Total flux	2210 lm	LOR	100%
Luminous efficacy	116 lm/W	Total power	19 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 6.81 in
Width: 6.81 in
Height: 7.99 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 19 W
Appliance Class: I

Protection

IP: 20