# Product data sheet

S150ST1-G2-38W-930-18°
SENSE150
NEKO



IP 54

Square recessed trimless downlight made of die-cast aluminium; System Power 42W; measurements 145X145(Aperture)x190mm; ceiling cutout of 147x147mm with a trimless mounting; ceiling thickness 12.5-25mm; rotation 355° and pivot max. 30°; CCT 3000K; high color rendering at an index of CRI90; after a lifetime of 50000h L80B10 min. 80% of the luminous flux with energy efficient CITIZEN LED Chips; 5 years warranty; beam characteristic with 18° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work with UGR<19; degree of housing protection IP54; light source replaceable by a qualified electrician; driver replaceable by a qualified electrician

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 2913 K |
| Nominal lamp power | 41.73 W | CRI | 92 |
| Total flux | 3116 lm | LOR | 100% |
| Luminous efficacy | 75 lm/W | Total power | 41.73 W |

### Mounting mode

Ceiling recessed

### Shape and measurements

Length: 5.91 in
Width: 5.91 in
Height: 7.48 in

### Adjustability

Rotatable, Tiltable

### Electric

System power: 41.73 W

### Protection

IP: 54