


Product data sheet

BEAM ME UP JR. SURFACE - Y3
MY3AWE-840M-D450-W
LIGHTNET



LED surface-mounted luminaire for walls and ceilings with setback lens optic set in a Décorative ring. Direct only light distribution or direct light distribution and indirect lighting corona. Luminaire body made of high-quality processed FRP (fiberglass reinforced plastic). Outer housing and Décorative reflector ring available in various finishes and combinations, e.g. white, silver, graphite, black, gold or copper coated. For surface options and combinations check Lightnet Surface Collection or Bi-Colour Selection. Microprismatic screen with optimized glare reduction especially for workplaces. Satin opal diffuser for general lighting with maximum transmittance and homogeneous lighting. Converter integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi). Colour temperatures 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning initial \leq MacAdam 3. Colour rendering CRI>80 or CRI>90. Sophisticated mounting system for easy installation and stable hold.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	12 W	CRI	82
Total flux	1630 lm	LOR	100%
Luminous efficacy	136 lm/W	Total power	12 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 17.72 in

Diameter: 17.72 in

Adjustability

Fixed

Electric

System power: 12 W

Protection