Product data sheet

VOLICA 2.0 LED SYSTEM ROLL 1500 5650LM 4000K ANODE C-0
010508.5L14.103
LUG



IP 20 IK 04

Luminaire with diffuser ordered separately as an accessory (20m roll). Decorative system luminaire for LED light sources; aluminum profile available in various colors, equipped with an efficient lighting system, optimized for indoor use. The luminaire is available in surface-mounted or suspended version, depending on the purchased accessories. Mounting: suspended, on wire suspension (on request), surface mounted Body: aluminum profile Power supply efficiency: >87% Power: 220-240V 50/60Hz Includes light source: yes Lifetime (L80B10): 100 000 h Lifetime (L90B10): 50 000 h Additional equipment: diffuser available as a 20m roll; diffuser must be ordered separately (accessory) Warranty: 5 years Application: offices, hotels, reception desks, galleries, auditorium, boutiques, museums

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	46 W	CRI	80
Total flux	5650 lm	LOR	100%
Luminous efficacy	123 lm/W	Total power	46 W

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Length: 59.06 in
Width: 2.36 in
Height: 3.15 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 46 W
Appliance Class: I

Protection

IP: 20
IK: 04