

Product data sheet

FLAT POLYMERO KREIS
311612.002.6.76
RZB




IP
40

IK
10

Series: Flat Polymero Kreis Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Base: metal, powder-coated. Diffuser fastening: push lock. Diffuser: plastic (polycarbonate), opal. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 515, H 98 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Impact Protection: IK10 (20 Joule) Luminaire flux LED: 2150lm System power: 19W Beam Angle: 121° Number of fittings B10A: 45 Number of fittings B16A: 80 Inrush current: 17A Unified Glare Ratio: 18,7 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	19 W	CRI	80
Total flux	2150 lm	LOR	100%
Luminous efficacy	113 lm/W	ULOR	11%
		Total power	19 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 3.86 in
Diameter: 20.28 in

Adjustability

Fixed

Electric

System power: 19 W

Protection

IP: 40
IK: 10