

# Product data sheet

UTA (BEADED)  
9.860.3042.06  
LEIPZIGER LEUCHTEN



Mounting height 4.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in color - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL-or DB -color without surcharge - Scope of supply includes hot galvanized and painted offset pole dia. 76 mm, and bracket.

## Light output 1



### 1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	78%
Lamp flux	4000 lm	Total flux	3119 lm
Luminous efficacy	35 lm/W	Total power	89 W
CCT	3400 K		
CRI	54		

## Mounting mode

Pole integrated, Ceiling mounted

## Shape and measurements

Height: 27.17 in  
Diameter: 23.62 in

## Design

Material impression: Matt  
Color of housing: White

## Electric

System power: 89 W  
Ballast: ECG

## Protection

Designation labels: CE

## Other operating numbers

Ambient temperature range: -13...95°F