



Product data sheet

NEPTUN LED V2 5500 PC-FROZEN E 21 IP66 840 / 1500X72X58MM,ZASILANIE PRZELOTOWE 16A , HT50
19.4220.1221.21
LUXIONA



Indoor luminaire. Assembly: directly mounted to ceiling construction or surface mounted on slings. The body material is polycarbonate.
Colour - RAL 9006 (grey). Luminaire dimensions: 1500 x 72 x 58 mm. Diffuser: PC-FROZEN (frozen polycarbonate). Beam angle: (C0-C180) / (C90-C270) - 116,4° / 102,2°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 100000 h L80/B10. Luminaire luminous flux: 6202,2 lm. Power of luminaire: 34,8 W. Luminaire's light efficiency: 178,2 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosp: >0,95. Circuit load capacity: 20 (B10), 32 (B16), 25 (C10), 40 (C16). Operating temperature range: -40 ÷ 50° C. Protection degree: IP66. Impact resistant: IK10. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0. Looping through power supply 16 A. The luminaire can be made in CLO (Constant Lumen Output) version.

Light output 1



1 x LED			
Nominal lamp power	34.8 W	LOR	83%
Lamp flux	6585 lm	Total flux	5496 lm
Luminous efficacy	189 lm/W	Total power	34.8 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 59.06 in

Width: 2.83 in

Height: 2.28 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 34.8 W

Appliance Class: I

Protection

IP: 66

IK: 10

Other operating numbers

Ambient temperature range: -40...122°F