



Product data sheet

JET 50 POST TOP LUMINAIRES
JE-20002-W-W40
LIGMAN




- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass lens - Maximum wind load resistance is 140 km/h

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	39 W	CRI	80
Total flux	2815 lm	LOR	100%
Luminous efficacy	72 lm/W	Total power	39 W

Light output 2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	39 W	CRI	80
Total flux	2815 lm	LOR	100%
Luminous efficacy	72 lm/W	Total power	39 W

Mounting mode

Standing / Bollard, Pole top mounted

Shape and measurements

Length: 6.30 in
Width: 23.62 in
Height: 118.11 in
Weight: 23.3 kg

Adjustability

Fixed

Glare protection

Glare protection: UGR < 19

Electric

System power: 78 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Design

Color of housing: Black, White, Silver gray

Protection

IP: 65

IK: 08

Surface temperature: 40°C