


Product data sheet

BASIC MAX SUSPENDED - G1
BG1ASE-840M-D600-U
LIGHTNET



LED pendant luminaire. Direct-indirect or direct-only light distribution. Luminaire body made of aluminum profile. 8 different diameters from 300mm to 2000mm. Surface white, silver, graphite, black, champagne or copper coated. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Microprismatic screen with optimized glare reduction especially for workplaces (up to max. DM1200). Opal diffuser made of acrylic glass, starting with DM1500 with opal stretch foil. Converter integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi). Colour temperatures 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning initial \leq MacAdam 3. Colour rendering CRI>80 or CRI>90. Height-adjustable central cord suspension (max. DM1500) or parallel cord suspension with transparent power supply cable, alternatively rod suspension. On request: Integration of emergency lighting components, sensor technology.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	52 W	CRI	82
Total flux	7250 lm	LOR	100%
Luminous efficacy	139 lm/W	Total power	52 W

Mounting mode

Pendant

Electric

System power: 52 W

Shape and measurements

Height: 23.62 in

Diameter: 23.62 in

Protection

Adjustability

Height adjustable