

# Product data sheet

NORA VIII (1-ARMED)  
9.778.3042.05  
LEIPZIGER LEUCHTEN



IP  
55

For medium light requirements, mounting height 3.50 - 4.00 m. - Impact-resistant clear or beaded polycarbonate attachment, UV-stabilized - Special reflector of premium highest-grade aluminium, burnished and anodized, for excellent illumination and glare protection - Aluminium luminaire body, inside finished in white paint, outside painted in colour - Aluminium unit carrier, painted white - Adapter jack connection - Available in any RAL or DB colour without surcharge - Scope of delivery includes special steel post/wall-mounted bracket, painted -Order post dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



### 1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	76%
Lamp flux	4000 lm	ULOR	2%
Luminous efficacy	34 lm/W	Total flux	3048 lm
CCT	3400 K	Total power	89 W
CRI	54		

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 11.81 in

Diameter: 21.26 in

## Electric

System power: 89 W

## Protection

IP: 55