

Product data sheet

FLAT POLYMERO
311592.002.1.78
RZB




IP
40

IK
03

Series: Flat Polymero Type of Protection: IP 40 Protection Class: I Voltage: 230 V / 50 Hz Base: metal, powder-coated. Diffuser fastening: push lock. Diffuser: plastic (PMMA), opal. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 460, H 120 Lamp: LED Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, 1-10V Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 1850lm System power: 18W Beam Angle: 117° Number of fittings B10A: 21 Number of fittings B16A: 34 Number of fittings C10A: 35 Number of fittings C16A: 57 Inrush current: 16A Unified Glare Ratio: 18,7 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	18 W	CRI	80
Total flux	1850 lm	LOR	100%
Luminous efficacy	103 lm/W	ULOR	10%
		Total power	18 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 4.72 in
Diameter: 18.11 in

Adjustability

Fixed

Electric

System power: 18 W

Protection

IP: 40
IK: 03