


# Product data sheet

SHOOTER  
9900-A-5-440-XX  
UNILAMP




Description SHOOTER is a robust ground-surface uplighter constructed with a robust aluminium housing and use of a thick safety glass cover. It is suitable for installation where a typical in-ground uplighter cannot or should not be used. It is designed to operate with high power LED light source. SHOOTER is protected from dust, water and possible harmful impact. This luminaire can be used to illuminate columns, panels, blocks, and ceilings from the low level. It's perfectly matched in any architectural environment. Anchor unit for concrete foundation is available as an accessory. Spec • Designed, Manufactured and Tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 die-cast aluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Safety glass cover. • Post-cured silicone gasket. • High quality LED module and driver. • High efficiency reflector. • M20 cable gland. • Pre-wired with outdoor cable. • Installation work has to be carried on according to the enclosed product manual.

## Light output 1




|                    |         |             |         |
|--------------------|---------|-------------|---------|
| 1 x LED            |         |             |         |
| Nominal lamp power | 8.4 W   | LOR         | 100%    |
| Lamp flux          | 140 lm  | ULOR        | 7%      |
| Luminous efficacy  | 17 lm/W | Total flux  | 140 lm  |
| CCT                | 0 K     | Total power | 10.45 W |
| CRI                | -49     |             |         |

## Light output 2




|                    |          |             |         |
|--------------------|----------|-------------|---------|
| 1 x LED            |          |             |         |
| Nominal lamp power | 8.4 W    | LOR         | 100%    |
| Lamp flux          | 910 lm   | ULOR        | 7%      |
| Luminous efficacy  | 108 lm/W | Total flux  | 910 lm  |
| CCT                | 0 K      | Total power | 10.57 W |
| CRI                | 83       |             |         |

Light output 3



|                    |         |             |         |
|--------------------|---------|-------------|---------|
| 1 x LED            |         |             |         |
| Nominal lamp power | 8 W     | LOR         | 100%    |
| Lamp flux          | 760 lm  | ULOR        | 7%      |
| Luminous efficacy  | 95 lm/W | Total flux  | 760 lm  |
| CCT                | 0 K     | Total power | 10.26 W |
| CRI                | -24     |             |         |

Light output 4



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| 1 x LED            |         |             |        |
| Nominal lamp power | 6.5 W   | LOR         | 100%   |
| Lamp flux          | 280 lm  | ULOR        | 7%     |
| Luminous efficacy  | 43 lm/W | Total flux  | 280 lm |
| CCT                | 0 K     | Total power | 8.72 W |
| CRI                | -29     |             |        |

Mounting mode

Standing / Bollard, Floor mounted

Shape and measurements

Length: 11.61 in

Width: 11.61 in

Height: 10.70 in

Adjustability

Fixed

Electric

System power: 40 W

Controller: DALI

Appliance Class: I

Protection

IP: 67

IK: 07