

Product data sheet


FL 20 MAXI LED 111000LM. PL43 ASY
5XA7693F3A1A
SOLAR



IP
66

Floodlight 20 maxi LED, flomlys, primær lysstyring med linse, fra PMMA, primær lystekn. skjerm: skjermglass, fra herdet sikkerhetsglass, klar, lysfordeling: PL43, lysutstråling: direkte strålende, monteringsstype: utenpåliggende, LED, LED-High Power, lysfluks: 111000 lm, lysutbytte: 123lm/W, lysfarge: 750, fargetemperatur: 5000K, forkoblingsenhet: HF Premium, styring: overopphetingsvern, elektronisk effektrduksjon, med klemme, 10-polet, maks. 2,5mm², strømtilkobling: 220..240V, AC, 50/60Hz, tilkoblet effekt: 903W, LED unit, armaturmodul, fra presstøpt aluminium, pulverbelagt, Siteco® metallisk grå (DB 702S), hussramme, fra presstøpt aluminium, pulverbelagt, Siteco® metallisk grå (DB 702S), festebeyle, fra stål, pulverbelagt, Siteco® metallisk grå (DB 702S), DALI, kapslingsgrad (totalt): IP66, beskyttelsesklasse (totalt): VK I (vernejording), testmerking: CE, ENEC under forberedelse, ballsikkerhet: ballsikker, pakningsenhet: 1 stykk

Light output 1 (integrated)



Lamp type	LED	CCT	5181 K
Nominal lamp power	903 W	CRI	70
Total flux	111004 lm	LOR	100%
Luminous efficacy	123 lm/W	Total power	903 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 28.74 in

Width: 38.39 in

Height: 4.53 in

Adjustability

Tiltable

Electric

System power: 903 W

Protection

IP: 66