


Product data sheet

LD238 6.4W 500MA WWB BB
LD238-E3-500-WWB-BB
LIGHTGRAPHIX



LD238 Ø68mm Surface mount spotlight. IP67. Constant Current. 6.4W 500mA 55° Extra wide with Besa Box Mount. The LD238 is a discreet surface mounted spotlight that is very compact in size but offers a powerful output and large range of features. There are 2 LED engines available. The E3 engine provides the ability to achieve a high output of up to 597lm, whilst the F1 offers a super warm colour temperature of 2200K. Featuring a single optic for superior beam quality, there are a range of beam angles available and a half or full cowl for low glare. With a choice of fixing options, including a ground spike, tree strap and surface mounted base, the versatile LD238 can be used in a range of exterior applications.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	6.4 W	CRI	85
Total flux	465 lm	LOR	100%
Luminous efficacy	73 lm/W	Total power	6.4 W

Mounting mode

Wall mounted, Ceiling mounted, Floor mounted

Shape and measurements

Height: 1.06 in
Diameter: 1.06 in

Adjustability

Rotatable, Tilttable, Free

Design

Material impression: Aluminum, Glass
Color of housing: Black, White, Anthracite / graphite, Silver gray

Electric

System power: 6.4 W
Controller: Dimmable 0..10V, Dimmable 1..10V, DMX, DALI
Appliance Class: III

Protection

IP: 67
Designation labels: CE

Other operating numbers

Ambient temperature range: -4...122°F