

Product data sheet


DEFINE LED SURFACE MOUNT LUMINAIRE
S122RDS-S1005D935-4F0-1E-UDD-F
COOPER LIGHTING



IP
47

Surface mount slot family in 2", 3", 4" and 5" housing sizes, Specifiable to the nearest 1', Multiple lensing options: flush satin, drop, regressed and asymmetric, Multiple lumen packages available, 0-10V dimming standard; DALI dimming available, 2700K, 3000K, 3500K, 4000K and 5000K correlated color temperatures, VividTune CCT tuning options from 3000K–5000K or 2700K-6500K, Integral Wavelinx and stand-alone sensors available, Customizable in-wall, in-ceiling and wall-to-ceiling corners available, DLC listed configurations available

Light output 1 (integrated)



| | | | |
|--------------------|---------|-------------|--------|
| Lamp type | LED | CCT | 3500 K |
| Nominal lamp power | 41.1 W | CRI | 90 |
| Total flux | 2900 lm | LOR | 100% |
| Luminous efficacy | 71 lm/W | Total power | 41.1 W |

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 48.00 in
Width: 2.00 in
Height: 0.39 in

Adjustability

Fixed

Electric

System power: 41.1 W

Protection

IP: 47