Product data sheet

NADJA II (WALL FITTING BEADED) 9.845.2052.06

LEIPZIGER LEUCHTEN








Recommended mounting height 4.00 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



| 1 x High pressure sodium vapour la | amp |
|------------------------------------|-----|
|------------------------------------|-----|

| Nominal lamp power | 100 W |
|--------------------|----------|
| Lamp flux | 10400 lm |
| Luminous efficacy | 71 lm/W |
| CCT | 2000 K |
| CRI | 25 |

LOR 78%
Total flux 8109 lm
Total power 115 W

Mounting mode

Wall mounted

Shape and measurements

Height: 20.08 in

Diameter: 20.08 in

Electric

System power: 115 W

Protection

IP: 55

Designation labels: CE, F