
# Product data sheet

LINEAR LIGHTING

V1-R0-90824-02OPD-4002530 X-LINE 1,25 M STAND-ALONE 25W 3000K DALI


VARTON



IP 40 IK 01

• Extruded aluminum luminaire • Standalone Application • Retail spaces • Administrative facilities Installation • Surface-mounted • Suspended Input voltage (AC, 50Hz), V: 176...264 AC frequency, Hz: 50 Flicker, %: 1 Climatic modification and category of placement: УХЛ4 Color rendering index: 80-89 Protection class: I Mounting method: Pendant Ingress protection (IP): IP40 Radiation angle: Radiation angle, °: 100 Impact resistance: IK01 Power factor: 0,95 https://www.varton.ru/products/lineynye-svetilniki-dlya-vnutrennego-osveshcheniya/x-line-odinochnye/x-line-1-25-m-odinochnye/cvetilnik-varton-x-line-1-25-m-25-vt-odinochnyy-podvesnoy-3000-k-1251x63x100-mm-ip40-ral9005-chernyy_1/

## Light output 1



1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 25 W | LOR | 100% |
| Lamp flux | 2500 lm | Total flux | 2500 lm |
| Luminous efficacy | 100 lm/W | Total power | 25 W |
| CCT | 3000 K | | |
| CRI | 80 | | |

### Mounting mode

Pendant

### Shape and measurements

Length: 49.25 in

Width: 2.48 in

Height: 3.94 in

### Adjustability

Fixed

### Electric

System power: 25 W

### Protection

IP: 40

IK: 01