Product data sheet

BHU LINEMED TRIANGLE LED P-4400-2200-ON-2-B-B-3-B E OPTICS-3L/PLX 53 840 L=1250MM
19.4060.1221.53
LUXIONA



IP 40 IK 04

Indoor luminaire. Assembly: mounted on wall. The body material is steel sheet. Colour - RAL 9003 (white). Dimensions: 1250 x 130 x 110 mm. Weight 5,98 kg. Diffuser: OPTICS (optical system based on lenses) / PLX (PMMA opal). The efficiency of the optical system is 73,16%. Beam angle: asymmetric light distribution. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 100000 (1) / 147000 (2) h L80/B10 (1) / L70/B10 (2). Luminaire luminous flux: 5010 lm. Power of luminaire: 35,3 W. Luminaire's light efficiency: 141,9 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 15 (B10), 24 (B16), 21 (C10), 35 (C16). Operating temperature range: 5 ÷ 30° C. Protection degree: IP40. Impact resistant: IK04. Protection against electric shock: I.

Light output 1



3 x LED

Nominal lamp power	14 W	LOR	52%
Lamp flux	2322 lm	Total flux	3653 lm
Luminous efficacy	166 lm/W	Total power	42 W
CCT	4000 K		
CRI	80		

Mounting mode

Wall mounted

Shape and measurements

Length: 49.21 in
Width: 5.12 in
Height: 4.33 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 42 W
Appliance Class: I

Protection

IP: 40
IK: 04

Other operating numbers

Ambient temperature range: 41...86°F