Product data sheet

SOLO 1100 GRAPHITE 590LM 3000K RA>80 TWILIGHT
7021986435542
SG ARMATUREN



IP 65 IK 10

Design: Hallvard Jakobsen Attractive, round wall luminaire with cross that can be installed both indoors and outdoors. Made of die-cast powder-coated aluminium. Diffuser made of UV-stabilised opal polycarbonate. Two inputs/outputs for cables, option of both visible and concealed cabling, and loopable quick clips. Several variants with integrated sensor or dimming relay. Corrosion-proof with 10-year warranty, IP65 and vandal-resistant rating IK10. Light distribution Direct Light technic LED 8W 3000K Ra>80 SDCM 3 L70/B10 >50,000 hrs Control/Dimming Twilight Protection Class II IP65 IK10 Fire protection class: 850°C - 30s Materials and finish Housing: Aluminium Colour: Graphite Optics: UV-stabilized polycarbonate Mounting/Connection Surface, Indoor / Outdoor Screwless terminal block Max. luminaires per circuit breaker: B10: 33, B16: 52, C10: 40, C16: 64

Light output 1



1 x LED

Nominal lamp power	8 W	LOR	100%
Lamp flux	590 lm	Total flux	590 lm
Luminous efficacy	74 lm/W	Total power	8 W
CCT	3000 K		
CRI	80		

Mounting mode

Wall mounted

Shape and measurements

Length: 10.63 in
Width: 4.84 in
Height: 10.63 in

Adjustability

Fixed

Electric

System power: 8 W
Appliance Class: I

Protection

IP: 65
IK: 10