Product data sheet

SOLO 1100 GRAPHITE TWILIGHT 570LM 3000K RA>80 ON/OFF 7021986435542

SG ARMATUREN












Design: Hallvard Jakobsen Attractive, round wall luminaire with cross that can be installed both indoors and outdoors. Made of die-cast powder-coated aluminium. Diffuser made of UV-stabilised opal polycarbonate. Two inputs/outputs for cables, option of both visible and concealed cabling, and loopable quick clips. Several variants with integrated sensor or dimming relay. Corrosion-proof with 10-year warranty, IP65 and vandal-resistant rating IK10. Light distribution Direct Light technic LED 11.5W 3000K Ra>80 SDCM 3 L70/B50 >50,000 hrs at Ta=25°C Control/Dimming On/Off Protection Class II IP65 IK10 Fire protection class: 850°C - 30s Energy and approvals A+ CE Materials and finish Housing: Aluminium Colour: Graphite Optics: UV-stabilized polycarbonate Mounting/Connection Surface, Indoor / Outdoor Screwless terminal block Max. luminaires per circuit breaker: B10: 33, B16: 52, C10: 40, C16: 64

Light output 1



1	Х	L	E	D

Nominal lamp power	11.5 W	LOR	100%
Lamp flux	570 lm	ULOR	8%
Luminous efficacy	50 lm/W	Total flux	570 lm
CCT	3000 K	Total power	11.5 W
CRI	80		

Mounting mode

Wall mounted

Shape and measurements

Length: 10.63 in Width: 4.84 in Height: 10.63 in

Adjustability

Fixed

Electric

System power: 11.5 W Appliance Class: I

Protection

IP: 65 IK: 10