

Product data sheet

SOLO 1100 GRAPHITE 590LM 3000K RA>80 TWILIGHT


7021986435542

SG ARMATUREN



Design: Hallvard Jakobsen Attractive, round wall luminaire with cross that can be installed both indoors and outdoors. Made of die-cast powder-coated aluminium. Diffuser made of UV-stabilised opal polycarbonate. Two inputs/outputs for cables, option of both visible and concealed cabling, and loopable quick clips. Several variants with integrated sensor or dimming relay. Corrosion-proof with 10-year warranty, IP65 and vandal-resistant rating IK10. Light distribution Direct Light technic LED 8W 3000K Ra>80 SDCM 3 L70/B10 >50,000 hrs Control/Dimming Twilight Protection Class II IP65 IK10 Fire protection class: 850°C - 30s Materials and finish Housing: Aluminium Colour: Graphite Optics: UV-stabilized polycarbonate Mounting/Connection Surface, Indoor / Outdoor Screwless terminal block Max. luminaires per circuit breaker: B10: 33, B16: 52, C10: 40, C16: 64

Light output 1



1 x LED

Nominal lamp power

8 W

LOR

100%

Lamp flux

590 lm

Total flux

590 lm

Luminous efficacy

74 lm/W

Total power

8 W

CCT

3000 K

CRI

80

Mounting mode

Wall mounted

Shape and measurements

Length: 10.63 in

Width: 4.84 in

Height: 10.63 in

Adjustability

Fixed

Electric

System power: 8 W

Appliance Class: I

Protection

IP: 65

IK: 10