


# Product data sheet

PH 6½-6 LED 3000K 96W  
5741094956  
LOUIS POULSEN



PH 5-4½ & PH 6½-6 Design : Poul Henningsen Concept : The trumpet-shaped top shade on the fixture provides illumination of the area above the three shades, which primarily direct the light downwards. A base reflector and a blue glare ring protect against glare from all angles. The strongest light is directly under the fixture. The shades have a matte white painted finish to ensure very comfortable lighting. Finish : White. Material : Shades: Spun aluminium. Anti-glare disc: Blue, spun aluminium. Struts: Rolled aluminium coloured. Mounting : Suspension type: Cable 3x0,75mm² or cable 3x0,75mm² & wire. Canopy: Yes. Cable length: PH 5-4½: 3m, PH 6½-6: 4m. Class : Ingress protection IP20. Electric shock protection I w. ground. Weight : Max. 6kg.

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	96 W	CRI	90
Total flux	4873 lm	LOR	100%
Luminous efficacy	51 lm/W	ULOR	10%
		Total power	96 W

## Mounting mode

Pendant

## Shape and measurements

Height: 12.52 in

Diameter: 18.35 in

## Adjustability

Fixed

## Electric

System power: 96 W

Appliance Class: I

## Protection

IP: 20