
# Product data sheet


VANCOUVER 7 LIGHT COLUMNS
VA-20041-W-W40
LIGMAN



IP 65 IK 08


- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Life time L90B10 Ta 25° 50,700 - Life time L80B10 Ta 50° > 63,500 - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency optical reflector - Clear toughened glass - Maximum wind load resistance is 160 km/h - Surge protection 10 kV

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 39.5 W | CRI | 80 |
| Total flux | 1671 lm | LOR | 100% |
| Luminous efficacy | 42 lm/W | ULOR | 100% |
| | | Total power | 39.5 W |

## Light output 2 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 20.7 W | CRI | 80 |
| Total flux | 1683 lm | LOR | 100% |
| Luminous efficacy | 81 lm/W | ULOR | 100% |
| | | Total power | 20.7 W |

### Mounting mode

Standing / Bollard, Pole top mounted

### Shape and measurements

Height: 157.48 in
Diameter: 9.45 in
Weight: 52.4 kg

### Adjustability

Fixed

### Glare protection

Glare protection: UGR < 19

### Electric

System power: 60.2 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

## Design

Color of housing: Black, White, Silver gray

## Protection

IP: 65

IK: 08

Surface temperature: 40°C