


Product data sheet

JET 34 WALL LUMINAIRES
JE-30413-M-40
LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour RGBW 30,40 - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Two cable entries for through wiring for JE-30393, JE-30413, JE-30383, JE-30403 - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency optical reflector - Clear toughened glass - Integral control gear

Light output 1 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	9.13 W	CRI	80
Total flux	481 lm	LOR	100%
Luminous efficacy	53 lm/W	Total power	9.13 W

Light output 2 (integrated)




Lamp type	LED	CCT	0 K
Nominal lamp power	9.19 W	CRI	-50
Total flux	69 lm	LOR	100%
Luminous efficacy	8 lm/W	Total power	9.19 W

Light output 3 (integrated)



Lamp type	LED	CCT	7247 K
Nominal lamp power	9.2 W	CRI	-18
Total flux	472 lm	LOR	100%
Luminous efficacy	51 lm/W	Total power	9.2 W

Light output 4 (integrated)



Lamp type	LED	CCT	0 K
Nominal lamp power	9.21 W	CRI	-29
Total flux	483 lm	LOR	100%
Luminous efficacy	52 lm/W	Total power	9.21 W

Mounting mode

Wall mounted

Shape and measurements

Length: 6.30 in

Width: 6.30 in

Height: 10.35 in

Weight: 5.1 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 36.73 W

Voltage: 230 V AC

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Protection

IP: 65

IK: 08

Surface temperature: 40°C