


Product data sheet

PH 3/2 ACADEMY E14 LED 2700K 3X5W
5741084869
LOUIS POULSEN



PH 3/2 Academy Design : Poul Henningsen Concept : The three lights on the fixture are designed based on the principle of a reflective threeshade system which directs the majority of the light downwards. The shades are made of mouth-blown opal three-layer glass, which is shiny on the top and sandblasted matt on the inside, giving a soft and diffuse light distribution. Finish : High lustre chrome plated. White opal glass. Material : Shades: Mouth-blown white opal glass. Frame: High lustre chrome plated, extruded brass. Suspension: High lustre chrome plated, extruded brass. Mounting : Suspension type: Cable 2x0,75mm². Canopy: Yes. Cable length: 4m. Class : Ingress protection IP20. Electric shock protection II w/o ground. Weight : Max. 6kg.

Light output 1



3 x LED			
Nominal lamp power	5 W	LOR	60%
Lamp flux	470 lm	ULOR	16%
Luminous efficacy	56 lm/W	Total flux	847 lm
CCT	2700 K	Total power	15 W
CRI	80		

Mounting mode

Pendant

Shape and measurements

Height: 9.84 in
Diameter: 26.77 in

Adjustability

Fixed

Electric

System power: 15 W
Appliance Class: I

Protection

IP: 20