

Product data sheet

LADOR 4 FLOODLIGHTS,PROJECTORS


LD-50032-E-40

LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour RGBW 30,40 - Drive current 24 VDC - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Thermal heat dissipation body - Single cable entry - Through wiring on request for LD-50021, LD-50031 - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Integral control gear

Light output 1 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	11 W	CRI	80
Total flux	882 lm	LOR	100%
Luminous efficacy	80 lm/W	Total power	11 W

Light output 2 (integrated)




Lamp type	LED	CCT	0 K
Nominal lamp power	11.9 W	CRI	-50
Total flux	99 lm	LOR	100%
Luminous efficacy	8 lm/W	Total power	11.9 W

Light output 3 (integrated)



Lamp type	LED	CCT	7247 K
Nominal lamp power	11.29 W	CRI	-18
Total flux	494 lm	LOR	100%
Luminous efficacy	44 lm/W	Total power	11.29 W

Light output 4 (integrated)



Lamp type	LED	CCT	0 K
Nominal lamp power	10.1 W	CRI	-29
Total flux	384 lm	LOR	100%
Luminous efficacy	38 lm/W	Total power	10.1 W

Mounting mode

Standing / Bollard, Wall mounted

Shape and measurements

Length: 5.71 in
Width: 5.71 in
Height: 7.68 in
Weight: 3 kg

Adjustability

Free

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 44.29 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: III

Protection

IP: 66
IK: 08
Surface temperature: 40°C