Product data sheet

PLAY DECO ASYMMETRICAL ROUND FIXED EMERGENCY
AG25-P7V9M2D1WG
LEDSC4



IP 54 IK 03

LedsC4 Play Deco Asymmetrical Round Fixed Emergency AG25-P7V9M2D1WG Downlight For downlighting. Structure material: Aluminium, Polycarbonate. Structure finish: White/Gold. Diffuser material: Methacrylate. Diffuser finish: Transparent. Warranty: 5 Years. Product net weight (Kg): 0.81 Product width or diameter (mm): 90 Product height (mm): 92 Ø of the hole for recessing (mm): 80 Permitted ceiling thickness: 0-25 Class 2. Luminaire not suitable for coating with insulation materials. Glow wire test: 850. IP: IP54. IK: IK03. LED. No. of lampholders or LEDs: 1. LED brand: CREE. Driver brand: VOSSLOH-SCHWABE. Maximum power of light source: 6.4W. Colour temperature: 2700K. Colour rendering index: 90. MacAdam Steps: 2. Hours of life: 50.000h L80B20. Photobiological risk: RG1. % de Flickering: <5%. Real flux (lm): 455. Real lm/W: 54. Voltage / frequency range: 100-240/50-60Hz. Voltage: 9. Equipment included: Yes. Total power: 8.5. Power factor: 0.90. Dimmable equipment included: DALI-2/PUSH. Emergency supply provision.

Light output 1 (emergency)



1 x LED

Nominal lamp power	4.11 W	LOR	100%
Lamp flux	220 lm	Total flux	220 lm
Luminous efficacy	54 lm/W	Total power	4.11 W
CCT	2700 K		
CRI	90		



1 x LED

Nominal lamp power	8.5 W	LOR	100%
Lamp flux	455 lm	Total flux	455 lm
Luminous efficacy	54 lm/W	Total power	8.5 W
CCT	2700 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.54 in
Width: 3.54 in
Height: 0.08 in

Electric

System power: 4.11-8.5 W
Appliance Class: II

Information regarding emergency functions

Emergency lighting only
Emergency sign: N/A

Adjustability

Fixed

Protection

IP: 54

IK: 03