



# Product data sheet

1550 CLESSIDRA 4 LED DIRECT-INDIRECT LIGHT 4000K CRI 90 15W CLD GRAPHITE  
420583-00  
DISANO



Housing: in die-cast aluminium. Diffuser: tempered glass, resistant to thermal shock and impact (UNI EN 12150-1:2001). Coating: pre-treatment of metal surface, polyester powder coating to ensure resistance to corrosion and salt spray fogs, UV stabilised. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. With degree of protection according to EN60529. Equipment: - during installation the frame stays attached via a safety hinge mechanism that prevents it from dropping down accidentally. - with wall mounting plate. - gasket in eco-friendly material. Easy installation: equipped for wall mount.

## Light output 1



1 x LED			
Nominal lamp power	15 W	LOR	100%
Lamp flux	555 lm	ULOR	50%
Luminous efficacy	37 lm/W	Total flux	555 lm
CCT	4000 K	Total power	15 W
CRI	90		

## Mounting mode

Wall mounted

## Shape and measurements

Length: 9.69 in  
Width: 6.57 in  
Height: 8.82 in

## Adjustability

Fixed

## Design

Material impression: Aluminum  
Color of housing: Anthracite / graphite

## Electric

System power: 15 W  
Appliance Class: I

## Protection

IP: 65  
IK: 07  
Designation labels: CE