Product data sheet


TAREK S
741858.004.76
RZB



IP 20 IK 07

Series: Tarek Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Housing: powder coated die cast aluminium. Rotates 356° horizontally and swivels 180° vertically, passive cooling. Reflector: faceted aluminium. LED included, with DALI adapter for 230V RZB 3 circuit DALI tracks, anti-reflective safety glass, ceiling mounted. Available Colours: silver, metallic Type of Installation: Track on ceiling Dimensions: L 290, B 120, H 178 Lamp: LED Life time: 50000 h (L90/B10) Colour Temperature: 2700K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Impact Protection: IK07 (2 Joule) Luminaire flux LED: 2750lm System power: 27W Beam Angle: 12° Number of fittings B10A: 45 Number of fittings B16A: 80 Inrush current: 17A Unified Glare Ratio: 16,1 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	27 W	CRI	80
Total flux	2750 lm	LOR	100%
Luminous efficacy	102 lm/W	Total power	27 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 4.72 in
Width: 11.42 in
Height: 7.01 in

Adjustability

Rotatable, Tiltable

Electric

System power: 27 W

Protection

IP: 20
IK: 07