Product data sheet


NEMO II MIDI 460LM 3000K RA>80 TRAILING EDGE DIMMING
7021986300727
SG ARMATUREN



IP 67 IK 10

Nemo II is a powerful in-ground luminaire for decorative and functional lighting of facades, gardens, patios, stairs and walls. Approved for 750 kg load. Nemo II comes in symmetric versions with deep black reflectors for very low glare, and asymmetric versions that directs the light toward a facade or a wall. Light distribution Direct (Beam angle: 32°) Light technic LED 9W 3000K Ra>80 SDCM 3 L80/B20 >50,000 hrs Control/Dimming Trailing edge dimming Protection Class I IP67 IK10 Materials and finish Housing: Aluminium and stainless steel Optics: PMMA (Acrylate) Mounting/Connection Recessed, Indoor / Outdoor Cable 1m Max. luminaires per circuit breaker: B10: 60, B16: 96, C10: 60, C16: 96

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	9 W	CRI	80
Total flux	460 lm	LOR	100%
Luminous efficacy	51 lm/W	ULOR	100%
		Total power	9 W

Mounting mode

Floor recessed

Shape and measurements

Length: 5.12 in
Width: 5.12 in
Height: 4.43 in

Adjustability

Fixed

Electric

System power: 9 W
Appliance Class: I

Protection

IP: 67
IK: 10