

Product data sheet

OUTDOOR LIGHTING
V1-S1-90506-40L05-6605027 TORNADO YARD 50W 2700K
VARTON




IP
66

IK
09

LED street light luminaire. Tool-free access to the driver. Adjustable spigot. Cast aluminum housing, tempered protective glass. Application: object without illumination requirement. Installation: pole and side-entry mounted (Ø48mm-60mm). AC frequency, Hz: 50 Flicker, %: 3 Climatic modification and category of placement: YXJ1 Protection class: I Suitable for top end size, mm: 48...60 Mounting method: Side-entry Ingress protection (IP): IP66 Impact resistance: IK09 Power factor: 0,95 Color rendering index: 70-79 Nominal voltage, V: 220...230 <https://www.varton.ru/products/ulichnoe-osveshchenie/tornado/tornado-yard-dlya-dvora/svetodiodnyy-svetilnik-var-ton-ulichnyy-tornado-yard-kreplenie-na-konsol-50-vt-2700-k-ra19005-chernyy/>

Light output 1



1 x LED			
Nominal lamp power	50 W	LOR	100%
Lamp flux	6100 lm	Total flux	6100 lm
Luminous efficacy	122 lm/W	Total power	50 W
CCT	2700 K		
CRI	70		

Mounting mode

Pole integrated

Shape and measurements

Length: 22.36 in
Width: 9.06 in
Height: 4.06 in

Adjustability

Fixed

Electric

System power: 50 W

Protection

IP: 66
IK: 09