


Product data sheet

MIRL LAY LED3800-830 M600Q WB EVG KA
42928726
ZUMTOBEL



Modular LED recessed luminaire with lens optic. Total power: 27.8 W, with LED converter; LED service life lasts 50000 h before luminous flux is reduced to 85% of the initial value. Chromaticity tolerance (initial MacAdam): 3. Luminaire luminous flux: 3620 lm, Luminaire efficacy: 130 lm/W. Colour rendering Ra > 80, colour temperature 3000 K. Symmetric very wide distribution luminaire (wide beam). Light control via square lens optic for glare-free light distribution with ; low dirt sensitivity and simple cleaning; Luminaire with external electrical connection; Installation as pure lay-in luminaire for modular ceilings with visible grid system; Luminaire wired with halogen-free leads; Dimensions: 598 x 598 x 38 mm, weight: 4.14 kg

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	27.8 W	CRI	80
Total flux	3620 lm	LOR	100%
Luminous efficacy	130 lm/W	Total power	27.8 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.54 in
Width: 23.54 in
Height: 1.50 in
Weight: 4.1 kg

Design

Color of housing: White

Electric

System power: 27.8 W
Voltage: 220-240 V AC
Appliance Class: I

Protection

IP: 40
Designation labels: CCC, CE, ENEC